IPv6 for your existing VoIP service

Sebastian Damm







Who we are, what we do

- Düsseldorf based VoIP provider (since 2004)
- Active in Germany and UK
- Private and Business customers
- VoIP and Mobile products
- Some 100k active customers
- Almost 100 million minutes each month

































General Setup w/ v6





Call Flow





Loadbalancer Additions

- Listening Interface
- Use correct socket
- RTPproxy handling
- Use registrar module



```
route[HANDLERTPPROXY] {
  if (is request()) {
    if (af == INET6 | is ipv6 reference($dd) ||
        ($dd == $null && is ipv6 reference($rd))) {
      if (is method("INVITE") && has body("application/sdp")) {
        if (af==INET6) {
          rtpproxy manage("ei-");
        } else if (is_ipv6_reference($dd) | |
                   ($dd == $null && is ipv6 reference($rd))) {
          rtpproxy manage("ie-");
      } else if (is_method("BYE|CANCEL")) {
        rtpproxy manage();
  } else {
    if (has_body("application/sdp") && (af == INET6 |
        is_ipv6_reference($sel(via[2].host)) | |
        is ipv6 reference($sel(via[2].received)))) {
      rtpproxy manage("-");
```



```
route[HANDLERTPPROXY] {
  if (is request()) {
    if (af == INET6 | is ipv6 reference($dd) ||
        ($dd == $null && is ipv6 reference($rd))) {
      if (is method("INVITE") && has body("application/sdp")) {
        if (af==INET6) {
          rtpproxy manage("ei-");
        } else if (is_ipv6_reference($dd) |
                   ($dd == $null && is ipv6 reference($rd))) {
          rtpproxy manage("ie-");
      } else if (is_method("BYE|CANCEL")) {
        rtpproxy manage();
  } else {
    if (has body("application/sdp") && (af == INET6 |
        is ipv6 reference($sel(via[2].host)) |
        is ipv6 reference($sel(via[2].received)))) {
      rtpproxy manage("-");
```



```
route[HANDLERTPPROXY] {
  if (is request()) {
    if (af == INET6 || is_ipv6_reference($dd) ||
        ($dd == $null && is ipv6 reference($rd))) {
      if (is method("INVITE") && has body("application/sdp")) {
        if (af==INET6) {
          rtpproxy manage("ei-");
        } else if (is_ipv6_reference($dd) |
                   ($dd == $null && is ipv6 reference($rd))) {
          rtpproxy manage("ie-");
      } else if (is method("BYE CANCEL")) {
        rtpproxy manage();
  } else {
    if (has body("application/sdp") && (af == INET6 |
        is ipv6 reference($sel(via[2].host)) |
        is ipv6 reference($sel(via[2].received)))) {
      rtpproxy manage("-");
```



```
route[HANDLERTPPROXY] {
  if (is request()) {
    if (af == INET6 | is ipv6 reference($dd) ||
        ($dd == $null && is ipv6 reference($rd))) {
      if (is method("INVITE") && has body("application/sdp")) {
        if (af==INET6) {
          rtpproxy manage("ei-");
        } else if (is_ipv6_reference($dd) |
                   ($dd == $null && is ipv6 reference($rd))) {
          rtpproxy manage("ie-");
      } else if (is_method("BYE|CANCEL")) {
        rtpproxy manage();
  } else {
    if (has body("application/sdp") && (af == INET6
        is_ipv6_reference($sel(via[2].host)) | |
        is ipv6 reference($sel(via[2].received)))) {
      rtpproxy manage("-");
```



```
route[HANDLERTPPROXY] {
  if (is_request()) {
    if (af == INET6 | is ipv6 reference($dd) ||
        ($dd == $null && is_ipv6_reference($rd))) {
      if (is method("INVITE") && has body("application/sdp")) {
        if (af==INET6) {
          rtpproxy manage("ei-");
        } else if (is_ipv6_reference($dd) |
                   ($dd == $null && is ipv6 reference($rd))) {
          rtpproxy manage("ie-");
      } else if (is_method("BYE|CANCEL")) {
        rtpproxy manage();
  } else {
    if (has_body("application/sdp") && (af == INET6 |
        is_ipv6_reference($sel(via[2].host)) | |
        is ipv6 reference($sel(via[2].received)))) {
      rtpproxy manage("-");
```



• "There is no NAT in IPv6.", they said. "Everything will be easier.", they said.



- "There is no NAT in IPv6.", they said.
 "Everything will be easier.", they said.
- What they didn't say: Home Routers will prevent connections from outside.




- "There is no NAT in IPv6.", they said.
 "Everything will be easier.", they said.
- What they didn't say: Home Routers will prevent connections from outside.
- Solution: Send NAT keepalives like you did in IPv4
 - but this time to every single device registered.




- "There is no NAT in IPv6.", they said. "Everything will be easier.", they said.
- What they didn't say: Home Routers will prevent connections from outside.
- Solution: Send NAT keepalives like you did in IPv4
 but this time to every single device registered.
- Since the proxy isn't IPv6 capable yet, the LB has to do it.






- Problem: MTU can change on the way to recipient
- Answer could end up on a different host






- Problem: MTU can change on the way to recipient
- Answer could end up on a different host






- Problem: MTU can change on the way to recipient
- Answer could end up on a different host






- Solution:
 root@host:~# sysctl -w net.ipv4.ip_no_pmtu_disc=1
- UDP packets get sent out without DF bit






- Solution: root@host:~# sysctl -w net.ipv4.ip_no_pmtu_disc=1
- UDP packets get sent out without DF bit






- IPv6: Fragmentation in routers not allowed
- Make sure the response ends up at the sending host!






- IPv6: Fragmentation in routers not allowed
- Make sure the response ends up at the sending host!






- IPv6: Fragmentation in routers not allowed
- Make sure the response ends up at the sending host!





• IPv6: Sender fragments packets





IPv6: Sender fragments packets




Watch out!

- IPv6 address vs. IPv6 address reference!
 - → ::1 vs. [::1] (ipops module)
- IPv6 packets carrying IPv4 addresses
- Field length for IP addresses in DB (15 vs. 39)
- Readiness
 - → Found 3 bugs in Kamailio (all fixed now)
 - → capture agent (Homer) not yet IPv6 capable
 - geoip module must be replaced
 - → (Soft)Phone Behavior in Dual Stack sometimes buggy



Okay, let's play!



- Used immediately after publishing the AAAA records
- Especially Speedport, snom, Asterisk, Softphones
- Help your customer support!
- But mainly: it just works.



Thank you for flying sipgate.

Work? http://www.sipgate.de/jobs
Hungry? http://lunch.sipgate.de

Sponsored Ads

